

► TASK Inspect pushrods, rocker arms, rocker arm pivots, and shafts for wear, bending, cracks, looseness, and blocked oil passages (orifices); determine needed action.

MAST
1B3

CDX Tasksheet Number: C021

Time off _____

Time on _____

Total time _____

1. Research the procedure and specifications for disassembling and inspecting the pushrods, rocker arms, pivots, and shafts in the appropriate service information.
 - a. List, or print off and attach to this sheet, the procedure for inspecting these parts:

2. Disassemble the rocker arm assemblies and clean them in a safe and environmentally approved way. This is commonly performed in a hot water spray machine.

3. Inspect the following parts:

- a. Pushrods: Worn ____ Bent ____ Cracked ____ Blocked passages ____
OK ____ (Check any that apply)
- b. Rocker arms: Worn ____ Bent ____ Cracked ____ Blocked passages ____
OK ____ (Check any that apply)
- c. Rocker arm studs: Worn ____ Bent ____ Cracked ____ OK ____
(Check any that apply)
- d. Pivots/shafts: Worn ____ Bent ____ Cracked ____ Blocked passages ____
OK ____ (Check any that apply)

4. Determine any necessary action(s):

5. Have your supervisor/instructor verify satisfactory completion of this procedure, any observations found, and any necessary action(s) recommended.

Performance Rating

CDX Tasksheet Number: C021

0

1

2

3

4

Supervisor/instructor signature _____ Date _____