

**► TASK** Inspect, remove, and/or replace power steering hoses and fittings.

**MAST**  
4B15

CDX Tasksheet Number: C183

Time off \_\_\_\_\_

Time on \_\_\_\_\_

Total time \_\_\_\_\_

1. Research the procedure to remove and install the power steering hoses and fittings. List the steps or print off the procedure:
2. Following the specified procedure, drain the power steering fluid into a clean container for proper disposal according to environmental guidelines and regulations.
3. Disconnect power steering hoses from both the power steering pump and the power steering box or rack. Plug any exposed fittings to prevent entry of dirt or debris.
4. Disconnect any retaining clips.
5. Remove power steering hoses from the vehicle and place on your workbench.
6. Examine the flexible hoses for cracks, splits, chafed surfaces, and distorted configurations (including hardening and loss of flexibility). List your observation(s):
7. Examine any steel tubes and fittings, check for heat damage, splits, kinking, damaged threads, or restrictions. List your observation(s):
8. Have your supervisor/instructor verify removal. Supervisor's/instructor's initials: \_\_\_\_\_
9. Following the specified procedure, reinstall the power steering hoses being careful not to cross-thread any fittings or damage any hoses or tubes.
10. Have your supervisor/instructor verify satisfactory completion of this procedure, any observations found, and any necessary action(s) recommended.

Performance Rating

CDX Tasksheet Number: C183

0

1

2

3

4

Supervisor/instructor signature \_\_\_\_\_ Date \_\_\_\_\_