CDX Tasksheet Number: C420

1. Obtain a quantity of fuel from the vehicle into the fuel container.

**NOTE** This is best done while performing a fuel pump volume test.

- 2. Pour 90 mL of gasoline into the graduated test tube.
- 3. Let this settle for a minute or two. Observe any contaminants in the fuel. List your observations:
- 4. Add 10 mL of water, bringing the total volume to 100 mL.
- 5. Cap the test tube tightly with a cork or other appropriate device.

**NOTE** Be sure you hold the cap firmly in place during this procedure. It will become pressurized, which could force the cap off, spraying fuel a considerable distance.

- 6. Slowly and carefully agitate the fuel/water mix for 30 seconds to bring the water into contact with the fuel. If there is any alcohol in the fuel, this will allow the water to be absorbed by the alcohol.
- 7. Allow the mixture to settle for a minute or two. Observe the level of the water in the bottom of the test tube. Anything higher than the initial 10 mL is the amount of alcohol in the fuel. List your observation(s):
- 8. Determine any necessary action(s):

- 9. Have your supervisor/instructor verify your observations. Supervisor's/instructor's initials:
- Carefully pour off the fuel in the test tube back to the fuel container. Make sure no water leaves the test tube.
- 11. Properly dispose of the remaining water/fuel mixture.

© 2018 Jones & Bartlett Learning, LLC, an Ascend Learning Company

Engine Performance 997

 $\ensuremath{\text{@}}$  2018 Jones & Bartlett Learning, LLC, an Ascend Learning Company **Performance Rating** CDX Tasksheet Number: C420 0 2 3 4 Supervisor/instructor signature \_ Date\_

998 Engine Performance