

**► TASK** Remove and reinstall/replace rotor.

**MAST**  
5D7

CDX Tasksheet Number: C806

Time off \_\_\_\_\_

Time on \_\_\_\_\_

Total time \_\_\_\_\_

1. Remove the rotor following the specified procedure.
2. Now would be a good time to inspect the rotor, if you haven't already, and consider refinishing it. Ask your supervisor/instructor if you are to inspect and/or refinish the rotor. If so, proceed to task C630.
3. If you are to reinstall this rotor, have your supervisor/instructor confirm removal. Supervisor's/instructor's initials: \_\_\_\_\_
4. When appropriate (most likely after refinishing), reinstall the rotor according to the manufacturer's recommendations.
5. If you had to remove the wheel bearing during disassembly, have your supervisor/instructor verify proper adjustment of the bearings.
  - a. Supervisor's/instructor's initials: \_\_\_\_\_
6. Have your supervisor/instructor verify satisfactory completion of this procedure, any observations found, and any necessary action(s) recommended.

**NOTE** If you came to this tasksheet from the "Disc Brake Inspection and Service" tasksheet, return to that tasksheet and continue where you left off.

© 2018 Jones & Bartlett Learning, LLC, an Ascend Learning Company

**Performance Rating**

CDX Tasksheet Number: C806

0

1

2

3

4

Supervisor/instructor signature \_\_\_\_\_ Date \_\_\_\_\_